

**Description**

cadmium plated steel philips recess - total panel thickness 0.420" - 0.449"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	27S314
Minimum Qty (MOQ):	4
NSN:	5325-01-013-1489



## P/N 27S3-14 Specifications

<b>Diameter:</b>	0.244 Inches Minimum And 0.256 Inches Maximum
<b>Securing Device Type:</b>	Washer
<b>Turnlock Stud Head Style:</b>	Stud Head
<b>Stud Assembly Style:</b>	Stud Assembly
<b>Distance From Engaging Member To Largest Bearing Surface Of Head:</b>	1.000 Inches Nominal
<b>Eyelet Outside Diameter:</b>	0.244 Inches Minimum And 0.250 Inches Maximum
<b>Eyelet Length:</b>	0.328 Inches Nominal
<b>Material Accommodated Thickness:</b>	0.780 Inches Minimum And 0.809 Inches Maximum
<b>Drive Type:</b>	Cross Recess
<b>Stud Head Height:</b>	0.073 Inches Nominal
<b>Material:</b>	Steel Overall

## How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/27S3-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.