

# P/N 2803

### **Description**

Screws part number

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

National Motor Freight:

SKU / Model:	2803
Minimum Qty (MOQ):	335 EA
NSN:	3110-00-151-9553
Schedule B:	7318.15.6080
ECCN:	EAR99

114820, Bearings / Bushings Noi Ball / Roller



<sup>\*</sup> See page 2 for technical characteristics

# P/N 2803 Specifications

Overall Width:	2.1875 Inches Nominal
Bore Diameter:	1.4375 Inches Nominal
Overall Outside Diameter:	3.6250 Inches Nominal
Backface Corner Radius:	0.0620 Inches Nominal
Standout Width:	0.3125 Inches Nominal
Cone Corner Radius:	0.0310 Inches Nominal
Cup Width:	1.5625 Inches Nominal
Retainer Fabrication Method:	Pressed
<b>Standard Tolerance Designation:</b>	Afbma Class 4
Special Features:	Operating Temperature Not To Exceed 121 Deg C/250 Deg F; Oil Hole And Groove In Cup; 0.0040 In. Min, 0.0060 In. Max Bench Lateral
Material:	Steel Overall
Style Designator:	Straight Bore, Double Cup, Single Cones, Steep Angle

## **How to Order**

Order this screws from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/2803">https://military-fasteners.com/screws/machine+screws/2803</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/machine+screws/2803">https://military-fasteners.com/screws/machine+screws/2803</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/machine+screws/2803">https://military-fasteners.com/screws/machine+screws/2803</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/machine+screws/2803">https://military-fasteners.com/screws/machine+screws/2803</a> and selecting the quantity you want then click "add to cart".