

Description

28S1-5 Turnlock Fastener Stud Assembly

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	28S15
Minimum Qty (MOQ):	5
NSN:	5325-00-565-5818
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



\* See page 2 for technical characteristics

# P/N 28S1-5 Specifications

Diameter:	0.302 Inches Nominal
Securing Device Type:	Washer
Turnlock Stud Head Style:	Flat Fillister
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.371 Inches Minimum And 0.381 Inches Maximum
Eyelet Outside Diameter:	0.519 Inches Minimum And 0.531 Inches Maximum
Stud Diameter:	0.124 Inches Minimum And 0.130 Inches Maximum
Material Accommodated Thickness:	0.150 Inches Minimum And 0.179 Inches Maximum
Drive Type:	Slotted
Stud Head Height:	0.092 Inches Nominal
Material:	Steel Comp 1009 Eyelet
Material:	Steel Comp 4037 Stud
Material:	Steel Pin
Material:	Steel Washer Or Steel Comp 305 Washer Or Steel Comp 304 Washer Or Steel Comp 302 Washer
Surface Treatment:	Cadmium Stud And Chromate Stud
Surface Treatment:	Cadmium Washer And Chromate Washer Or Passivate Washer
Surface Treatment:	Cadmium Pin And Chromate Pin

## How to Order

Order this turnlock fastener stud asssembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/28S1-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.