

Description

slotted, fillister head, stud assembly, dia: 1/2", steel, cadmium and chromate plated, total panel thickness 0.090" - 0.119

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[1128000-3](#)

| | |
|-------------------------|--|
| SKU / Model: | 28S143 |
| Minimum Qty (MOQ): | 2 |
| NSN: | 5325-01-150-4867 |
| ECCN: | EAR99 |
| National Motor Freight: | 066440, Fasteners Curtain / Snap Metal |



* See page 2 for technical characteristics

P/N 28S14-3 Specifications

| | |
|---|--|
| Diameter: | 0.489 Inches Minimum And 0.511 Inches Maximum |
| Securing Device Type: | Washer |
| Turnlock Stud Head Style: | Fillister |
| Stud Assembly Style: | Stud Assembly |
| Eyelet Outside Diameter: | 0.519 Inches Minimum And 0.531 Inches Maximum |
| Stud Diameter: | 0.305 Inches Minimum And 0.315 Inches Maximum |
| Material Accommodated Thickness: | 0.090 Inches Minimum And 0.119 Inches Maximum |
| Drive Type: | Slotted |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall |

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/28S14-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.