

**Description**

Diameter: 19/64", steel eyelet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	28S144
Minimum Qty (MOQ):	2
NSN:	5325-00-523-1376
Schedule B:	7318.15.5030
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



\* See page 2 for technical characteristics

## P/N 28S14-4 Specifications

<b>Diameter:</b>	0.300 Inches Nominal
<b>Securing Device Type:</b>	Washer
<b>Turnlock Stud Head Style:</b>	Fillister
<b>Stud Assembly Style:</b>	Stud Assembly
<b>Distance From Engaging Member To Largest Bearing Surface Of Head:</b>	0.341 Inches Nominal
<b>Eyelet Outside Diameter:</b>	0.500 Inches Nominal
<b>Stud Diameter:</b>	0.124 Inches Minimum And 0.130 Inches Maximum
<b>Material Accommodated Thickness:</b>	0.120 Inches Minimum And 0.149 Inches Maximum
<b>Drive Type:</b>	Cross Recess
<b>Material:</b>	Steel Comp 4037 Stud
<b>Material:</b>	Steel Eyelet
<b>Material:</b>	Steel Pin
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall

## How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/28S14-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.