

Description

Diameter: 19/64", steel eyelet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	28S144
Minimum Qty (MOQ):	2
NSN:	5325-00-523-1376
Schedule B:	7318.15.5030
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



* See page 2 for technical characteristics

P/N 28S14-4 Specifications

Diameter:	0.300 Inches Nominal
Securing Device Type:	Washer
Turnlock Stud Head Style:	Fillister
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.341 Inches Nominal
Eyelet Outside Diameter:	0.500 Inches Nominal
Stud Diameter:	0.124 Inches Minimum And 0.130 Inches Maximum
Material Accommodated Thickness:	0.120 Inches Minimum And 0.149 Inches Maximum
Drive Type:	Cross Recess
Material:	Steel Comp 4037 Stud
Material:	Steel Eyelet
Material:	Steel Pin
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall

How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/28S14-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.