


**Description**

Diameter: 1/2", steel overall

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	28S147
Minimum Qty (MOQ):	5
NSN:	5325-01-208-8129
Schedule B:	7318.15.5030
ECCN:	EAR99
National Motor Freight:	066440, Fasteners Curtain / Snap Metal



\* See page 2 for technical characteristics

## P/N 28S14-7 Specifications

<b>Diameter:</b>	0.489 Inches Minimum And 0.511 Inches Maximum
<b>Securing Device Type:</b>	Ring
<b>Turnlock Stud Head Style:</b>	Flat Fillister
<b>Stud Assembly Style:</b>	Stud Assembly
<b>Eyelet Outside Diameter:</b>	0.519 Inches Minimum And 0.531 Inches Maximum
<b>Stud Diameter:</b>	0.124 Inches Minimum And 0.130 Inches Maximum
<b>Drive Type:</b>	Cross Recess
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response Overall

## How to Order

Order this turnlock fastener stud assembly from our inventory online by visiting <https://military-fasteners.com/studs/turnlock+fastener+stud+assemblies/28S14-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.