

Description

Fastener Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	29930
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-253-5615
Schedule B:	7326.90.8588
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N 29930 Specifications

Fastener Length:	0.250 Inches Nominal
Head Style:	Round
Head Diameter:	0.193 Inches Minimum And 0.211 Inches Maximum
Head Height:	0.075 Inches Minimum And 0.086 Inches Maximum
Pilot Diameter:	0.092 Inches Minimum And 0.096 Inches Maximum
Pilot Length:	0.047 Inches Nominal
Features Provided:	Casehardened
Nonmachine Thread Style:	Drive Screw (type U)
Nonmachine Nominal Thread Diameter:	0.114 Inches
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/drive+screws/29930> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.