

**Description**

Collar part number

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |                     |
|-------------------------|---------------------|
| SKU / Model:            | 2DCC6               |
| Minimum Qty (MOQ):      | 50                  |
| NSN:                    | 5320-00-804-0488    |
| Schedule B:             | 7616.99.5090        |
| ECCN:                   | EAR99               |
| National Motor Freight: | 013630, Alum Rivets |



\* See page 2 for technical characteristics

# P/N 2DC-C6 Specifications

|  |  |
|--|--|
| Collar Outside Diameter:                       | 0.300 Inches Minimum And 0.302 Inches Maximum  |
| Collar Overall Height:                         | 0.228 Inches Minimum And 0.236 Inches Maximum  |
| Collar Inside Diameter:                        | 0.188 Inches Minimum And 0.190 Inches Maximum  |
| Collar Style:                                  | Configural Type  |
| Material:                                      | Aluminum Alloy Overall   |
| Surface Treatment:                             | Anodize Overall Or Chromate Overall  |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec Single Treatment Response Overall Or Mil-c-5541 Mil Spec Single Treatment Response Overall |

## How to Order

Order this collar from our inventory online by visiting [https://military-fasteners.com/collars/pin\\_rivet+collars/2DC-C6](https://military-fasteners.com/collars/pin_rivet+collars/2DC-C6) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.