

# **P/N 2DC-EU05**

### **Description**

Collar part number

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: 2DCEU05

Minimum Qty (MOQ): 15 EA

NSN: 5320-00-284-2150

Schedule B: 7318.23.0000

ECCN: EAR99

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc



<sup>\*</sup> See page 2 for technical characteristics

# **P/N 2DC-EU05 Specifications**

Collar Outside Diameter:	0.256 Inches Minimum And 0.260 Inches Maximum
Collar Overall Height:	0.197 Inches Minimum And 0.208 Inches Maximum
Lubrication:	Dry Film
Collar Inside Diameter:	0.168 Inches Minimum And 0.173 Inches Maximum
Collar Style:	Configural Type
Heat Treatment:	Annealed Overall
Material:	Iron Alloy 660 Overall
Surface Treatment:	Passivate Overall

## **How to Order**

Order this collar from our inventory online by visiting <a href="https://military-fasteners.com/collars/pin\_rivet+collars/2DC-EU05">https://military-fasteners.com/collars/pin\_rivet+collars/2DC-EU05</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/collars/pin\_rivet+collars/2DC-EU05">https://military-fasteners.com/collars/pin\_rivet+collars/2DC-EU05</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/collars/pin\_rivet+collars/2DC-EU05">https://military-fasteners.com/collars/pin\_rivet+collars/2DC-EU05</a> and selecting the quantity you want then click "add to cart".