

Description

2 position, 2 pole, standard lever, screw terminal

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[MS24524-30](#)

SKU / Model:	2TL16
Minimum Qty (MOQ):	1
NSN:	5930-00-660-3950
ECCN:	9A991
National Motor Freight:	061300, Circuit Breaker / Switch Noi



* See page 2 for technical characteristics

P/N 2TL1-6 Specifications

Body Style:	Bushing Mount
Overall Length:	1.340 Inches Maximum
Overall Height:	2.560 Inches Nominal
Overall Width:	0.910 Inches Maximum
Bushing Length:	0.470 Inches Nominal
Body Length:	1.340 Inches Maximum
Body Width:	0.910 Inches Maximum
Body Height:	0.970 Inches Nominal
Actuator Style:	Round
Actuator Diameter:	0.240 Inches Nominal
Actuator Height:	0.660 Inches Minimum And 0.720 Inches Maximum
Actuator Position-action Relationship:	Up Position Maintained And Down Position Momentary
Maximum Voltage Rating In Volts:	115.0 Ac And 28.0 Dc
Inclosure Type:	Fully Inclosed
Mounting Method:	Threaded Bushing
Features Provided:	Actuator Seal
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.469 Inches
Nonpile-up Contact Arrangement:	2 Pole, Single Throw, Normally Open, Momentary Action Single Switch Unit
Contact Load Current Rating At Maximum Rated Voltage:	18.000 Amperes Resistive Dc And 10.000 Amperes Inductive Dc And 5.000 Amperes Lamp Dc And 11.000 Amperes Resistive Ac And 8.000 Amperes Inductive Ac And 2.000 Amperes Lamp Ac
Thread Series Designator:	Uns
Terminal Type And Quantity:	4 Screw

How to Order

Order this toggle switch from our inventory online by visiting <https://military-fasteners.com/electrical/toggle+switches/2TL1-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.