

Description

Fastener Length: 1/2", Thread: 10-32, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | 3003T09P01 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5306-00-904-1606 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N 3003T09P01 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.370 Inches Minimum And 0.380 Inches Maximum |
| Fastener Length: | 0.480 Inches Minimum And 0.500 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.115 Inches Minimum And 0.135 Inches Maximum |
| Width Between Flats: | 0.367 Inches Minimum And 0.376 Inches Maximum |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 0.110 Inches Minimum And 0.120 Inches Maximum |
| Features Provided: | Finished Head |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 130000 Pounds Per Square Inch |
| Hardness Rating: | 26.0 Rockwell C Minimum Overall |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5737 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this screws from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3003T09P01> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.