

P/N 307

Description

Thread Size: 0-5/8"

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: 307

Minimum Qty (MOQ): 10

NSN: 6240-00-155-7784

National Motor Freight: 109550, Lamps(bulbs) Elec Incandescent Noi



^{*} See page 2 for technical characteristics

P/N 307 Specifications

Overall Length: 2.000 Inches Maximum Fillament Designation: C-2v Light Output Rating: 21.000 Spherical Candlepower Nominal Single Rating Average Life Rating In Hours: 500.0 Fillament Heavy Duty Service Rating: Not Rated Deep Submergence Systems Programs (dssp.); Helicopter, Mh-53e; Truck, Fire/crash P15; Test Consoles, Mini-sace; Aircraft, Car-130h, Mc-130h, Ec-130, Hc-130l; Truck, Fire/crash P2; Aircraft, C-18a, Ec-18b; Aircraft, Osprey V-22a, Air Force; Helicopter Hh-53h Pave Low; Aircraft, Osprey V-22a, Marine Corps Emitted Light Characteristic: Colorless Light Center Length: 1.125 Inches Nominal Voltage Rating: 8.000 Volts Nominal Wattage Rating: 1.8200 Watts Bulb Style: 5 (straight Side) Bulb Designator: 5 (straight Side) Bulb Light Transmission Characteristic: 5 (straight Side) Current Rating For Which Designed: 0.670 Amperes Nominal Rated Average Life: Hours Burning Position: Any Acceptable Specification/standard Data: 08108-307 Manufacturers Standard		
Light Output Rating:21.000 Spherical Candlepower Nominal Single RatingAverage Life Rating In Hours:500.0Filament Heavy Duty Service Rating:Not RatedDeep Submergence Systems Programs (dssp); Helicopter, Mh-53e; Truck, Fire/crash P15; Test Consoles, Mini-sace; Aircraft, (ac-130h, Mc-130h, Ec-130h, Hc-130); Truck, Fire/crash P2; Aircraft, C-18a, Ec-18b; Aircraft, Osprey V-22a, Air Force; Helicopter Hh-53h Pave Low; Aircraft, Osprey V-22a, Marine CorpsEmitted Light Characteristic:ColorlessLight Center Length:1.125 Inches NominalVoltage Rating:28.000 Volts NominalWattage Rating:18.200 WattsBase Style:Single Contact Bayonet CandelabraBulb Style:5 (straight Side)Bulb Designator:5 (straight Side)Bulb Light Transmission Characteristic:7 ransparentCurrent Rating For Which Designed:0.670 Amperes NominalRated Average Life:HoursBurning Position:Any Acceptable	Overall Length:	2.000 Inches Maximum
Average Life Rating In Hours: Filament Heavy Duty Service Rating: Not Rated Deep Submergence Systems Programs (dssp); Helicopter, Mh-53e; Truck, Fire/crash P15; Test Consoles, Mini-sace; Aircraft, (ac-130h, End Item Identification: Mc-130h, Ec-130, Hc-130); Truck, Fire/crash P2; Aircraft, C-18a, Ec-18b; Aircraft, Osprey V-22a, Air Force; Helicopter Hh-53h Pave Low; Aircraft; Osprey V-22a, Marine Corps Emitted Light Characteristic: Colorless Light Center Length: Voltage Rating: 8.000 Volts Nominal Wattage Rating: 8.200 Watts Base Style: Single Contact Bayonet Candelabra Bulb Style: S (straight Side) Bulb Designator: S-8 Bulb Light Transmission Characteristic: Current Rating For Which Designed: Rated Average Life: Hours Burning Position: Any Acceptable	Filament Designation:	C-2v
Filament Heavy Duty Service Rating:Not RatedDeep Submergence Systems Programs (dssp); Helicopter, Mh-53e; Truck, Fire/crash P15; Test Consoles, Mini-sace; Aircraft, (ac-130h, Mc-130h, Ec-130, Hc-130); Truck, Fire/crash P2; Aircraft, C-18a, Ec-18b; Aircraft, Osprey V-22a, Air Force; Helicopter Hh-53h PaveEmitted Light Characteristic:ColorlessLight Center Length:1.125 Inches NominalVoltage Rating:28.000 Volts NominalWattage Rating:18.200 WattsBase Style:Single Contact Bayonet CandelabraBulb Style:5 (straight Side)Bulb Designator:5-8Bulb Light Transmission Characteristic:TransparentCurrent Rating For Which Designed:0.670 Amperes NominalRated Average Life:HoursBurning Position:Any Acceptable	Light Output Rating:	21.000 Spherical Candlepower Nominal Single Rating
Deep Submergence Systems Programs (dssp); Helicopter, Mh-53e; Truck, Fire/crash P15; Test Consoles, Mini-sace; Aircraft, (ac-130h, Mc-130h, Ec-130h, Ec-130h; Truck, Fire/crash P2; Aircraft, C-18a, Ec-18b; Aircraft, Osprey V-22a, Air Force; Helicopter Hh-53h Pave Low; Aircraft, Osprey V-22a, Marine Corps Emitted Light Characteristic: Colorless Light Center Length: 1.125 Inches Nominal Voltage Rating: 28.000 Volts Nominal Wattage Rating: 18.200 Watts Base Style: Single Contact Bayonet Candelabra Bulb Style: S (straight Side) Bulb Designator: S-8 Bulb Light Transmission Characteristic: Current Rating For Which Designed: 0.670 Amperes Nominal Rated Average Life: Hours Burning Position: Any Acceptable	Average Life Rating In Hours:	500.0
End Item Identification:Mc-130h, Ec-130); Truck, Fire/crash P2; Aircraft, C-18a, Ec-18b; Aircraft, Osprey V-22a, Air Force; Helicopter Hh-53h Pave Low; Aircraft, Osprey V-22a, Marine CorpsEmitted Light Characteristic:ColorlessLight Center Length:1.125 Inches NominalVoltage Rating:28.000 Volts NominalWattage Rating:18.200 WattsBase Style:Single Contact Bayonet CandelabraBulb Style:S (straight Side)Bulb Designator:S-8Bulb Light Transmission Characteristic:TransparentCurrent Rating For Which Designed:0.670 Amperes NominalRated Average Life:HoursBurning Position:Any Acceptable	Filament Heavy Duty Service Rating:	Not Rated
Light Center Length: Voltage Rating: 28.000 Volts Nominal Wattage Rating: 18.200 Watts Base Style: Single Contact Bayonet Candelabra Bulb Style: S (straight Side) Bulb Designator: S-8 Bulb Light Transmission Characteristic: Current Rating For Which Designed: 0.670 Amperes Nominal Rated Average Life: Hours Any Acceptable	End Item Identification:	Mc-130h, Ec-130, Hc-130); Truck, Fire/crash P2; Aircraft, C-18a, Ec-18b; Aircraft, Osprey V-22a, Air Force; Helicopter Hh-53h Pave
Voltage Rating:28.000 Volts NominalWattage Rating:18.200 WattsBase Style:Single Contact Bayonet CandelabraBulb Style:5 (straight Side)Bulb Designator:5-8Bulb Light Transmission Characteristic:TransparentCurrent Rating For Which Designed:0.670 Amperes NominalRated Average Life:HoursBurning Position:Any Acceptable	Emitted Light Characteristic:	Colorless
Wattage Rating: 18.200 Watts Base Style: Single Contact Bayonet Candelabra Bulb Style: S (straight Side) Bulb Designator: S-8 Bulb Light Transmission Characteristic: Transparent Current Rating For Which Designed: 0.670 Amperes Nominal Rated Average Life: Hours Burning Position: Any Acceptable	Light Center Length:	1.125 Inches Nominal
Base Style: Single Contact Bayonet Candelabra Bulb Style: S (straight Side) Bulb Designator: S-8 Bulb Light Transmission Characteristic: Transparent Characteristic: 0.670 Amperes Nominal Rated Average Life: Hours Burning Position: Any Acceptable	Voltage Rating:	28.000 Volts Nominal
Bulb Style: S (straight Side) Bulb Designator: S-8 Bulb Light Transmission Characteristic: Transparent Current Rating For Which Designed: 0.670 Amperes Nominal Rated Average Life: Hours Burning Position: Any Acceptable	Wattage Rating:	18.200 Watts
Bulb Light Transmission Characteristic: Current Rating For Which Designed: 0.670 Amperes Nominal Rated Average Life: Hours Burning Position: Any Acceptable	Base Style:	Single Contact Bayonet Candelabra
Bulb Light Transmission Characteristic: Current Rating For Which Designed: Rated Average Life: Burning Position: Any Acceptable	Bulb Style:	S (straight Side)
Characteristic: Current Rating For Which Designed: Rated Average Life: Burning Position: I ransparent 0.670 Amperes Nominal Hours Any Acceptable	Bulb Designator:	S-8
Rated Average Life: Hours Burning Position: Any Acceptable	_	Transparent
Burning Position: Any Acceptable	Current Rating For Which Designed:	0.670 Amperes Nominal
	Rated Average Life:	Hours
Specification/standard Data: 08108-307 Manufacturers Standard	Burning Position:	Any Acceptable
	Specification/standard Data:	08108-307 Manufacturers Standard

How to Order

Order this lamp, incandescent from our inventory online by visiting https://military-fasteners.com/electrical/incandescent+lamps/307 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/electrical/incandescent+lamps/307 and selecting the quantity you