

Description

Fastener Length: 31/32", Thread: 10-32, Head Width: 3/32", Thread Length: 53/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3107266
Minimum Qty (MOQ):	1 EA
NSN:	5305-00-009-0467
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N 310726-6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.820 Inches Minimum And 0.840 Inches Maximum
Fastener Length:	0.960 Inches Minimum And 0.980 Inches Maximum
Head Style:	Headless (setscrew)
Point Length:	0.120 Inches Minimum And 0.160 Inches Maximum
Point Diameter:	0.080 Inches Minimum And 0.085 Inches Maximum
Point Style:	Dog
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.190 Inches
Width Across Flats:	0.094 Inches Minimum And 0.096 Inches Maximum
Thread Quantity Per Inch:	32
Material:	Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 304l Overall Or Steel Comp 305 Overall Or Steel Comp 309 Overall Or Steel Comp 310 Overall Or Steel Comp 316 Overall Or Steel Comp 316l Overall Or Steel Comp 317 Overall Or Steel Comp 321 Overall Or Steel Comp 347 Overall
Material Document And Classification:	Qq-s-763 Fed Spec All Material Responses Overall
Thread Series Designator:	Unf

How to Order

Order this adjusting screw from our inventory online by visiting <https://military-fasteners.com/screws/setscrews/310726-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.