

Description

Fastener Length: 29/64", Thread: 6-32, Thread Length: "

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	31722001
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-349-9124
Schedule B:	7318.15.6080
ECCN:	EAR99



\* See page 2 for technical characteristics

## P/N 3172200-1 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.370 Inches Minimum
<b>Fastener Length:</b>	0.440 Inches Minimum And 0.460 Inches Maximum
<b>Head Style:</b>	Hexagon Countersunk Undercut
<b>Bottom Countersink Diameter:</b>	0.250 Inches Nominal
<b>Head Height:</b>	0.180 Inches Minimum And 0.220 Inches Maximum
<b>Width Between Flats:</b>	0.250 Inches Nominal
<b>Internal Drive Style:</b>	Clutch Type li
<b>Nominal Thread Diameter:</b>	0.138 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Hardness Rating:</b>	31.0 Rockwell C Minimum And 39.0 Rockwell C Maximum
<b>Countersink Angle:</b>	88.0 Degrees Minimum And 92.0 Degrees Maximum
<b>Screw Material:</b>	Steel Comp Xm-12
<b>Screw Material Document And Classification:</b>	Ams5659 Assn Std Single Material Response
<b>Screw Surface Treatment:</b>	Chromate
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this special screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3172200-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.