

Description

Fastener Length: 29/64", Thread: 6-32, Thread Length: "

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	31722001
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-349-9124
Schedule B:	7318.15.6080
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N 3172200-1 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.370 Inches Minimum
Fastener Length:	0.440 Inches Minimum And 0.460 Inches Maximum
Head Style:	Hexagon Countersunk Undercut
Bottom Countersink Diameter:	0.250 Inches Nominal
Head Height:	0.180 Inches Minimum And 0.220 Inches Maximum
Width Between Flats:	0.250 Inches Nominal
Internal Drive Style:	Clutch Type li
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Hardness Rating:	31.0 Rockwell C Minimum And 39.0 Rockwell C Maximum
Countersink Angle:	88.0 Degrees Minimum And 92.0 Degrees Maximum
Screw Material:	Steel Comp Xm-12
Screw Material Document And Classification:	Ams5659 Assn Std Single Material Response
Screw Surface Treatment:	Chromate
Thread Series Designator:	Unc

How to Order

Order this special screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3172200-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.