

**Description**

Fastener Length: 1/2", Hole Diameter: 1/16", Thread: 5/16-24, Thread Length: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | 317232                                    |
| Minimum Qty (MOQ):      | 5 EA                                      |
| NSN:                    | 5306-00-551-1788                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N 317232 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 0.490 Inches Minimum And 0.510 Inches Maximum                       |
| <b>Fastener Length:</b>                               | 0.490 Inches Minimum And 0.510 Inches Maximum                       |
| <b>Head Style:</b>                                    | Double Hexagon W/hole   |
| <b>Head Height:</b>                                   | 0.365 Inches Minimum And 0.385 Inches Maximum                       |
| <b>Width Between Flats:</b>                           | 0.367 Inches Minimum And 0.376 Inches Maximum                       |
| <b>Extended Washer Diameter:</b>                      | 0.490 Inches Minimum And 0.510 Inches Maximum                       |
| <b>Extended Washer Thickness:</b>                     | 0.070 Inches Minimum And 0.080 Inches Maximum                       |
| <b>Hole Diameter:</b>                                 | 0.060 Inches Nominal  |
| <b>Nominal Thread Diameter:</b>                       | 0.312 Inches  |
| <b>Hole Quantity:</b>                                 | 4   |
| <b>Hole Type:</b>                                     | Drilled   |
| <b>Features Provided:</b>                             | Finished Head   |
| <b>Thread Quantity Per Inch:</b>                      | 24  |
| <b>Hardness Rating:</b>                               | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall |
| <b>Hole Configuration Style:</b>                      | Double Hexagon Longitudinal Hole                                    |
| <b>Material:</b>                                      | Steel Comp 8740 Overall   |
| <b>Material Document And Classification:</b>          | Ams 6322 Assn Std Single Material Response Overall                  |
| <b>Surface Treatment:</b>                             | Cadmium Overall   |
| <b>Surface Treatment Document And Classification:</b> | Ams 2400 Assn Std Single Treatment Response Overall                 |
| <b>Thread Series Designator:</b>                      | Unf   |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/317232> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.