

P/N 3176207-C-018

Description

Fastener Length: 1/2", Thread: 6-32, Head Width: 3/32", Thread Length: 1/2"

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: 3176207C018

Minimum Qty (MOQ): 5 EA

NSN: 5305-01-081-1239

Schedule B: 7318.15.6080

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N 3176207-C-018 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.500 Inches Nominal
Fastener Length:	0.500 Inches Nominal
Head Style:	Fillister
Head Diameter:	0.218 Inches Minimum And 0.226 Inches Maximum
Head Height:	0.134 Inches Minimum And 0.138 Inches Maximum
Locking Feature:	Patch Threads
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.138 Inches
Width Across Flats:	0.109 Inches Nominal
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	38.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Minimum Yield Strength:	155000 Pounds Per Square Inch
Special Features:	Critical Item Hydrogen Embrittlement Relief Required
Material:	Steel Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Zinc Overall
Surface Treatment Document And Classification:	Qq-z-325,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this cap screw from our inventory online by visiting https://military-fasteners.com/screws/socket+head+cap+screws/3176207-C-018 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/socket+head+cap+screws/3176207-C-018 and selecting the