

Description

Fastener Length: 5/8", Thread: 10-24, Head Width: 1/8", Thread Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3176207C061
Minimum Qty (MOQ):	15 EA
NSN:	5305-01-034-1762
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N 3176207-C-061 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.625 Inches Maximum
Fastener Length:	0.625 Inches Nominal
Head Style:	Flat Chamfer
Head Diameter:	0.303 Inches Minimum And 0.312 Inches Maximum
Head Height:	0.185 Inches Minimum And 0.190 Inches Maximum
Locking Feature:	Patch Threads
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.190 Inches
Width Across Flats:	0.156 Inches Nominal
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	38.0 Rockwell C Nominal Overall
Minimum Yield Strength:	155000 Pounds Per Square Inch
Special Features:	Critical Item Hydrogen Embrittlement Relief Required
Material:	Steel Overall Or Steel Corrosion Resisting Overall
Material Document And Classification:	Qq-z-325,type 2 Cl 3 Fed Spec Single Material Response Overall Or Qq-p-35 Fed Spec Single Material Response Overall
Surface Treatment:	Zinc Overall
Surface Treatment Document And Classification:	Qq-z-325,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/3176207-C-061> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.