

**Description**

Fastener Length: 5/8", Thread: 10-24, Head Width: 1/8", Thread Length: 5/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | 3176207C061                               |
| Minimum Qty (MOQ):      | 15 EA                                     |
| NSN:                    | 5305-01-034-1762                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N 3176207-C-061 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 0.625 Inches Maximum  |
| <b>Fastener Length:</b>                               | 0.625 Inches Nominal  |
| <b>Head Style:</b>                                    | Flat Chamfer  |
| <b>Head Diameter:</b>                                 | 0.303 Inches Minimum And 0.312 Inches Maximum   |
| <b>Head Height:</b>                                   | 0.185 Inches Minimum And 0.190 Inches Maximum   |
| <b>Locking Feature:</b>                               | Patch Threads   |
| <b>Internal Drive Style:</b>                          | Hexagon   |
| <b>Nominal Thread Diameter:</b>                       | 0.190 Inches  |
| <b>Width Across Flats:</b>                            | 0.156 Inches Nominal  |
| <b>Thread Quantity Per Inch:</b>                      | 24  |
| <b>Minimum Tensile Strength:</b>                      | 180000 Pounds Per Square Inch   |
| <b>Hardness Rating:</b>                               | 38.0 Rockwell C Nominal Overall   |
| <b>Minimum Yield Strength:</b>                        | 155000 Pounds Per Square Inch   |
| <b>Special Features:</b>                              | Critical Item Hydrogen Embrittlement Relief Required  |
| <b>Material:</b>                                      | Steel Overall Or Steel Corrosion Resisting Overall  |
| <b>Material Document And Classification:</b>          | Qq-z-325,type 2 Cl 3 Fed Spec Single Material Response Overall Or Qq-p-35 Fed Spec Single Material Response Overall |
| <b>Surface Treatment:</b>                             | Zinc Overall  |
| <b>Surface Treatment Document And Classification:</b> | Qq-z-325,ty 2,cl 3 Fed Spec Single Treatment Response Overall   |
| <b>Thread Series Designator:</b>                      | Unc   |

## How to Order

Order this cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/3176207-C-061> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.