

## P/N 3176207-C-090

## **Description**

Fastener Length: 1-", Thread: 1/4-20, Head Width: 3/16", Thread Length: 0-63/64

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: 3176207C090

Minimum Qty (MOQ): 10

NSN: 5305-01-029-1530

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









# **P/N 3176207-C-090 Specifications**

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.900 Inches Minimum And 1.000 Inches Maximum
Fastener Length:	1.000 Inches Nominal
Head Style:	Flat Chamfer
Head Diameter:	0.365 Inches Minimum And 0.375 Inches Maximum
Head Height:	0.244 Inches Minimum And 0.250 Inches Maximum
Locking Feature:	Strip Fastener
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.250 Inches
Width Across Flats:	0.188 Inches Nominal
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	170000 Pounds Per Square Inch
Hardness Rating:	38.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Minimum Yield Strength:	150000 Pounds Per Square Inch
Surface Finish:	63.0 Microinches Bearing Surface Of Head
Material:	Steel Overall
Surface Treatment:	Zinc Overall And Chromate Overall
Surface Treatment Document And Classification:	Astm B633,ty 2 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unc

## **How to Order**

Order this socket head cap screws from our inventory online by visiting <a href="https://military-fasteners.com/screws/socket+head+cap+screws/3176207-C-090">https://military-fasteners.com/screws/socket+head+cap+screws/3176207-C-090</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.