

P/N 3176207-C-123

Description

Fastener Length: 1-1/64", Thread: 5/16-18, Head Width: 1/4", Thread Length: 0-57/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3176207C123
Minimum Qty (MOQ):	50
NSN:	5305-01-032-9198
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N 3176207-C-123 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.889 Inches Minimum And 1.000 Inches Maximum
Fastener Length:	1.000 Inches Nominal
Head Style:	Flat Chamfer
Head Diameter:	0.457 Inches Minimum And 0.469 Inches Maximum
Head Height:	0.306 Inches Minimum And 0.312 Inches Maximum
Locking Feature:	Patch Threads
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.312 Inches
Width Across Flats:	0.250 Inches Nominal
Thread Quantity Per Inch:	18
Minimum Tensile Strength:	170000 Pounds Per Square Inch
Material:	Plastic Polyamide Locking Feature
Material:	Steel Uns K03104 Fastener
Material Document And Classification:	Astm A574 Assn Std Single Material Response Overall
Material Document And Classification:	Mil-f-18240 Mil Spec Single Material Response Locking Feature
Surface Treatment:	Zinc Overall And Chromate Overall
Surface Treatment Document And Classification:	Astm B633,ty2 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this socket head cap screws from our inventory online by visiting https://military-fasteners.com/screws/socket+head+cap+screws/3176207-C-123 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.