

Description

Fastener Length: 3-1/4", Thread: 1/4-18, Head Width: 1/4", Thread Length: 1-45/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3176207C132
Minimum Qty (MOQ):	95 EA
NSN:	5305-01-095-8966
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N 3176207-C-132 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.710 Inches Nominal
Fastener Length:	3.250 Inches Nominal
Head Style:	Flat Chamfer
Head Diameter:	0.457 Inches Minimum And 0.469 Inches Maximum
Head Height:	0.306 Inches Minimum And 0.312 Inches Maximum
Locking Feature:	Patch Threads
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.312 Inches
Width Across Flats:	0.250 Inches Nominal
Thread Quantity Per Inch:	18
Minimum Tensile Strength:	170 Pounds Per Square Inch
Hardness Rating:	38.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Special Features:	Critical Item Hydrogen Embrittlement Relief Required
Material:	Steel Overall
Surface Treatment:	Zinc Overall
Surface Treatment Document And Classification:	Qq-z-325,type 2,class 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/3176207-C-132> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.