



Military-Fasteners.com

P/N 3176207-C-207

## Description

Fastener Length: 1-1/2", Thread: 3/8-14, Head Width: 3/8", Thread Length: 1-1/2"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	3176207C207
Minimum Qty (MOQ):	250 EA
NSN:	5305-01-031-8467
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N 3176207-C-207 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	1.357 Inches Minimum And 1.500 Inches Maximum
<b>Fastener Length:</b>	1.500 Inches Nominal
<b>Head Style:</b>	Flat Chamfer
<b>Head Diameter:</b>	0.642 Inches Minimum And 0.656 Inches Maximum
<b>Head Height:</b>	0.430 Inches Minimum And 0.438 Inches Maximum
<b>Locking Feature:</b>	Patch Threads
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.437 Inches
<b>Width Across Flats:</b>	0.375 Inches Nominal
<b>Thread Quantity Per Inch:</b>	14
<b>Minimum Tensile Strength:</b>	170000 Pounds Per Square Inch
<b>Hardness Rating:</b>	38.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
<b>Minimum Yield Strength:</b>	150000 Pounds Per Square Inch
<b>Surface Finish:</b>	32.0 Microinches Threads
<b>Surface Finish:</b>	63.0 Microinches Bearing Surface Of Head
<b>Surface Finish:</b>	63.0 Microinches Grip
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Zinc Overall
<b>Surface Treatment Document And Classification:</b>	Astm B633 Assn Std Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/3176207-C-207> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.