

## P/N 3176207-C-209

### **Description**

Fastener Length: 2-", Thread: 3/8-14, Head Width: 3/8", Thread Length: 1-3/8"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: 3176207C209

Minimum Qty (MOQ): 250 EA

NSN: 5305-01-060-3382

Schedule B: 7318.15.6080

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N 3176207-C-209 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.380 Inches Minimum
Fastener Length:	2.000 Inches Nominal
Head Style:	Fillister
Head Diameter:	0.642 Inches Minimum And 0.656 Inches Maximum
Head Height:	0.430 Inches Minimum And 0.438 Inches Maximum
Locking Feature:	Patch Threads
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.437 Inches
Width Across Flats:	0.375 Inches Nominal
Features Provided:	Casehardened
Thread Quantity Per Inch:	14
Hardness Rating:	37.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Threads
Special Features:	Critical Item Hydrogen Embrittlement Relief Required
Material:	Steel Overall
Surface Treatment:	Zinc Overall
Surface Treatment Document And Classification:	Qq-z-325,type 2,class 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

## **How to Order**

Order this cap screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/socket+head+cap+screws/3176207-C-209">https://military-fasteners.com/screws/socket+head+cap+screws/3176207-C-209</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.