

Description

Fastener Length: 1-3/4", Thread: 1/2-13, Head Width: 3/8", Thread Length: 1-3/4", 3176207 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3176207C264
Minimum Qty (MOQ):	100
NSN:	5305-01-071-1300
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N 3176207-C-264 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.750 Inches Nominal
Fastener Length:	1.750 Inches Nominal
Head Style:	Fillister
Head Diameter:	0.735 Inches Minimum And 0.750 Inches Maximum
Head Height:	0.492 Inches Minimum And 0.500 Inches Maximum
Locking Feature:	Patch Threads
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.500 Inches
Width Across Flats:	0.375 Inches Nominal
Thread Quantity Per Inch:	13
Minimum Tensile Strength:	24100 Pounds Per Square Inch
Material:	Steel Overall
Surface Treatment:	Zinc Overall
Surface Treatment Document And Classification:	Qq-z-325,type 2,cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this socket head cap screws from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/3176207-C-264> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.