

Description

Fastener Length: 3-", Thread: 1/2-13, Head Width: 3/8", Thread Length: 1-1/2

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3176207C269
Minimum Qty (MOQ):	1
NSN:	5305-01-081-2464
Schedule B:	7318.15.2010
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N 3176207-C-269 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.500 Inches Minimum
Fastener Length:	3.000 Inches Nominal
Head Style:	Fillister
Head Diameter:	0.735 Inches Minimum And 0.750 Inches Maximum
Head Height:	0.492 Inches Minimum And 0.500 Inches Maximum
Locking Feature:	Patch Threads
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.500 Inches
Width Across Flats:	0.375 Inches Nominal
Thread Quantity Per Inch:	13
Minimum Tensile Strength:	170000 Pounds Per Square Inch
Hardness Rating:	38.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Minimum Yield Strength:	150000 Pounds Per Square Inch
Special Features:	Ritical Item Hydrogen Embrittlement Relief Required
Material:	Steel Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Zinc Overall
Surface Treatment Document And Classification:	Qq-z-325,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this socket head cap screws from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/3176207-C-269> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.