

Description

Fastener Length: 3-1/2", Thread: 5/8-11, Head Width: 1/2", Thread Length: 1-3/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3176207C324
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-081-7376
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N 3176207-C-324 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.750 Inches Minimum
Fastener Length:	3.500 Inches Nominal
Head Style:	Fillister
Head Diameter:	0.921 Inches Minimum And 0.938 Inches Maximum
Head Height:	0.616 Inches Minimum And 0.625 Inches Maximum
Locking Feature:	Patch Threads
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.625 Inches
Width Across Flats:	0.500 Inches Nominal
Thread Quantity Per Inch:	11
Minimum Tensile Strength:	170000 Pounds Per Square Inch
Hardness Rating:	38.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Minimum Yield Strength:	150000 Pounds Per Square Inch
Special Features:	Critical Item Hydrogen Embrittlement Relief Required
Material:	Steel Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Surface Treatment:	Zinc Overall
Surface Treatment Document And Classification:	Qq-z-325,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/3176207-C-324> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.