

Description

Fastener Length: 2-", Thread: 3/4-10, Head Width: 5/8", Thread Length: 2-"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3176207C368
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-096-6162
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	096640, Screws, Iron Or Steel

NO IMAGE
AVAILABLE

P/N 3176207-C-368 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	2.000 Inches Nominal
Fastener Length:	2.000 Inches Nominal
Head Style:	Flat Chamfer
Head Diameter:	1.107 Inches Minimum And 1.125 Inches Maximum
Head Height:	0.740 Inches Minimum And 0.750 Inches Maximum
Locking Feature:	Patch Threads Or Strip Threads
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.750 Inches
Width Across Flats:	0.625 Inches Nominal
Thread Quantity Per Inch:	10
Minimum Tensile Strength:	170000 Pounds Per Square Inch
Hardness Rating:	38.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Material:	Plastic Locking Feature
Material:	Steel Fastener
Surface Treatment:	Zinc Fastener
Surface Treatment Document And Classification:	Astm B633 Ty 2 Cl 3 Assn Std Single Treatment Response Fastener
Thread Series Designator:	Unc

How to Order

Order this cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/3176207-C-368> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.