

P/N 3176207-C-368

Description

Fastener Length: 2-", Thread: 3/4-10, Head Width: 5/8", Thread Length: 2-"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: 3176207C368

Minimum Qty (MOQ): 5 EA

NSN: 5305-01-096-6162

Schedule B: 7318.15.6080

ECCN: 9A991

National Motor Freight: 096640, Screws, Iron Or Steel



^{*} See page 2 for technical characteristics

P/N 3176207-C-368 Specifications

| Thread Class: | 3a |
|--|---|
| Thread Direction: | Right-hand |
| Thread Length: | 2.000 Inches Nominal |
| Fastener Length: | 2.000 Inches Nominal |
| Head Style: | Flat Chamfer |
| Head Diameter: | 1.107 Inches Minimum And 1.125 Inches Maximum |
| Head Height: | 0.740 Inches Minimum And 0.750 Inches Maximum |
| Locking Feature: | Patch Threads Or Strip Threads |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.750 Inches |
| Width Across Flats: | 0.625 Inches Nominal |
| Thread Quantity Per Inch: | 10 |
| Minimum Tensile Strength: | 170000 Pounds Per Square Inch |
| Hardness Rating: | 38.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall |
| Material: | Plastic Locking Feature |
| Material: | Steel Fastener |
| Surface Treatment: | Zinc Fastener |
| Surface Treatment Document And Classification: | Astm B633 Ty 2 Cl 3 Assn Std Single Treatment Response Fastener |
| Thread Series Designator: | Unc |

How to Order

Order this cap screw from our inventory online by visiting https://military-fasteners.com/screws/socket+head+cap+screws/3176207-C-368 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.