

**Description**

Fastener Length: 2-", Thread: 3/4-10, Head Width: 5/8", Thread Length: 2-"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	3176207C368
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-096-6162
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	096640, Screws, Iron Or Steel

NO IMAGE  
AVAILABLE

## P/N 3176207-C-368 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	2.000 Inches Nominal
<b>Fastener Length:</b>	2.000 Inches Nominal
<b>Head Style:</b>	Flat Chamfer
<b>Head Diameter:</b>	1.107 Inches Minimum And 1.125 Inches Maximum
<b>Head Height:</b>	0.740 Inches Minimum And 0.750 Inches Maximum
<b>Locking Feature:</b>	Patch Threads Or Strip Threads
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.750 Inches
<b>Width Across Flats:</b>	0.625 Inches Nominal
<b>Thread Quantity Per Inch:</b>	10
<b>Minimum Tensile Strength:</b>	170000 Pounds Per Square Inch
<b>Hardness Rating:</b>	38.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
<b>Material:</b>	Plastic Locking Feature
<b>Material:</b>	Steel Fastener
<b>Surface Treatment:</b>	Zinc Fastener
<b>Surface Treatment Document And Classification:</b>	Astm B633 Ty 2 Cl 3 Assn Std Single Treatment Response Fastener
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/3176207-C-368> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.