

## P/N 3176207-C-368

### **Description**

Fastener Length: 2-", Thread: 3/4-10, Head Width: 5/8", Thread Length: 2-"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: 3176207C368

Minimum Qty (MOQ): 5 EA

NSN: 5305-01-096-6162

Schedule B: 7318.15.6080

ECCN: 9A991

National Motor Freight: 096640, Screws, Iron Or Steel



<sup>\*</sup> See page 2 for technical characteristics

# **P/N 3176207-C-368 Specifications**

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	2.000 Inches Nominal
Fastener Length:	2.000 Inches Nominal
Head Style:	Flat Chamfer
Head Diameter:	1.107 Inches Minimum And 1.125 Inches Maximum
Head Height:	0.740 Inches Minimum And 0.750 Inches Maximum
Locking Feature:	Patch Threads Or Strip Threads
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.750 Inches
Width Across Flats:	0.625 Inches Nominal
Thread Quantity Per Inch:	10
Minimum Tensile Strength:	170000 Pounds Per Square Inch
Hardness Rating:	38.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Material:	Plastic Locking Feature
Material:	Steel Fastener
Surface Treatment:	Zinc Fastener
Surface Treatment Document And Classification:	Astm B633 Ty 2 Cl 3 Assn Std Single Treatment Response Fastener
Thread Series Designator:	Unc

## **How to Order**

Order this cap screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/socket+head+cap+screws/3176207-C-368">https://military-fasteners.com/screws/socket+head+cap+screws/3176207-C-368</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.