

Description

Fastener Length: 2-3/4", Thread: 3/4-10, Head Width: 5/8", Thread Length: 2-"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | 3176207C371 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-01-081-2478 |
| Schedule B: | 7318.15.6080 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N 3176207-C-371 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 2.000 Inches Minimum |
| Fastener Length: | 2.750 Inches Nominal |
| Head Style: | Fillister |
| Head Diameter: | 1.107 Inches Minimum And 1.125 Inches Maximum |
| Head Height: | 0.740 Inches Minimum And 0.750 Inches Maximum |
| Locking Feature: | Patch Threads |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.750 Inches |
| Width Across Flats: | 0.625 Inches Nominal |
| Thread Quantity Per Inch: | 10 |
| Minimum Tensile Strength: | 170000 Pounds Per Square Inch |
| Hardness Rating: | 38.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall |
| Minimum Yield Strength: | 150000 Pounds Per Square Inch |
| Special Features: | Critical Item Hydrogen Embrittlement Relief Required |
| Material: | Steel Overall |
| Material Document And Classification: | 66 Fed Std Single Material Response Overall |
| Surface Treatment: | Zinc Overall |
| Surface Treatment Document And Classification: | Qq-z-325,type 2,class 3 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unc |

How to Order

Order this cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/3176207-C-371> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.