

Description

connector, ring terminal 14-16 awg 1/4, pidg, blue, crimp

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------------------|
| SKU / Model: | 321045 |
| Minimum Qty (MOQ): | 50 |
| NSN: | 5940-01-036-1472 |
| National Motor Freight: | 061680, Elec Wiring Plugs Etc |



* See page 2 for technical characteristics

P/N 321045 Specifications

| | |
|---|---|
| Overall Length: | 1.078 Inches |
| Overall Width: | 0.469 Inches |
| Material Thickness: | 0.033 Inches |
| Maximum Conductor Size Accommodated: | 14 Awg |
| Electrical Insulation Feature: | Insulating Sleeve |
| Mounting Method Style: | Ring |
| Mounting Hole Diameter: | 0.260 Inches |
| Mounting Tongue Width: | 0.469 Inches |
| Mounting Facility Thickness: | 0.033 Inches |
| Identification Code Color: | Blue |
| Basic Shape Style: | Crimp |
| Conductor Accommodation Type: | Recessed Barrel Single End |
| Material: | Copper Overall Except Insulation |
| Material: | Plastic Polyamide Insulation |
| Material Document And Classification: | Qq-c-576 Fed Spec Single Material Response Overall Except Insulation |
| Surface Treatment: | Tin Overall Except Insulation Single Layer |
| Surface Treatment Document And Classification: | Mil-t-10727 Mil Spec Single Treatment Response Overall Except Insulation Single Layer |

How to Order

Order this wire terminal from our inventory online by visiting <https://military-fasteners.com/electrical/lug+terminals/321045> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.