



Military-Fasteners.com

P/N 329025

Description

Fastener Length: 9/16", Hole Diameter: ", Thread: 1/4-28, Thread Length: 35/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	329025
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-803-8296
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N 329025 Specifications

Thread Direction:	Right-hand
Thread Length:	0.481 Inches Minimum And 0.552 Inches Maximum
Fastener Length:	0.552 Inches Minimum And 0.572 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.320 Inches Minimum And 0.340 Inches Maximum
Width Between Flats:	0.304 Inches Minimum And 0.313 Inches Maximum
Extended Washer Diameter:	0.428 Inches Minimum And 0.448 Inches Maximum
Extended Washer Thickness:	0.060 Inches Minimum And 0.070 Inches Maximum
Hole Diameter:	0.062 Inches Nominal
Nominal Thread Diameter:	0.250 Inches
Hole Quantity:	4
Hole Type:	Drilled
Features Provided:	Finished Head
Nonstandard Thread Pitch Diameter:	+0.2213/+0.2238 Inches
Thread Quantity Per Inch:	28
Hardness Rating:	24.0 Rockwell C Minimum Overall And 36.0 Rockwell C Maximum Overall
Minimum Yield Strength:	85000 Pounds Per Square Inch
Hole Configuration Style:	Double Hexagon Longitudinal Hole
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5732 Assn Std Single Material Response Overall
Precious Material:	Silver
Surface Treatment:	Silver Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/329025> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.