

Description

Diameter: 3/8", steel eyelet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3506SC38AK3B
Minimum Qty (MOQ):	5 EA
NSN:	5325-00-321-2623
Schedule B:	7318.15.5030
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N 3506-SC38A-K3B Specifications

Diameter:	0.373 Inches Minimum And 0.377 Inches Maximum
Turnlock Stud Head Style:	Flat Fillister
Stud Assembly Style:	Stud Assembly
Distance From Engaging Member To Largest Bearing Surface Of Head:	0.380 Inches Nominal
Eyelet Outside Diameter:	0.375 Inches Nominal
Eyelet Length:	0.375 Inches Nominal
Material Accommodated Thickness:	0.064 Inches Nominal
Drive Type:	Slotted
Stud Head Height:	0.275 Inches Minimum And 0.295 Inches Maximum
Special Features:	Color Black No.37038 Fed-std-595
Material:	Steel Comp 8620 Stud
Material:	Steel Ejector Spring
Material:	Steel Eyelet
Material Document And Classification:	Qq-w-470 Fed Spec Single Material Response Ejector Spring
Surface Treatment:	Chromium Overall
Surface Treatment Document And Classification:	Mil-c-14538 Mil Spec Single Treatment Response Overall

How to Order

Order this stud from our inventory online by visiting <https://military-fasteners.com/studs/plain+studs/3506-SC38A-K3B> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.