

**Description**

Diameter: 3/8", steel eyelet

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	3506SC38AK3B
Minimum Qty (MOQ):	5 EA
NSN:	5325-00-321-2623
Schedule B:	7318.15.5030
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N 3506-SC38A-K3B Specifications

<b>Diameter:</b>	0.373 Inches Minimum And 0.377 Inches Maximum
<b>Turnlock Stud Head Style:</b>	Flat Fillister
<b>Stud Assembly Style:</b>	Stud Assembly
<b>Distance From Engaging Member To Largest Bearing Surface Of Head:</b>	0.380 Inches Nominal
<b>Eyelet Outside Diameter:</b>	0.375 Inches Nominal
<b>Eyelet Length:</b>	0.375 Inches Nominal
<b>Material Accommodated Thickness:</b>	0.064 Inches Nominal
<b>Drive Type:</b>	Slotted
<b>Stud Head Height:</b>	0.275 Inches Minimum And 0.295 Inches Maximum
<b>Special Features:</b>	Color Black No.37038 Fed-std-595
<b>Material:</b>	Steel Comp 8620 Stud
<b>Material:</b>	Steel Ejector Spring
<b>Material:</b>	Steel Eyelet
<b>Material Document And Classification:</b>	Qq-w-470 Fed Spec Single Material Response Ejector Spring
<b>Surface Treatment:</b>	Chromium Overall
<b>Surface Treatment Document And Classification:</b>	Mil-c-14538 Mil Spec Single Treatment Response Overall

## How to Order

Order this stud from our inventory online by visiting <https://military-fasteners.com/studs/plain+studs/3506-SC38A-K3B> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.