

Description

Fastener Length: 3-5/32", Hole Diameter: 3/64", Thread: 8-32, Thread Length: 0-63/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | 3562210 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5305-00-106-6529 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |



* See page 2 for technical characteristics

P/N 35622-10 Specifications

| | |
|--|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.980 Inches Minimum And 1.020 Inches Maximum |
| Fastener Length: | 3.150 Inches Minimum And 3.170 Inches Maximum |
| Head Style: | Fillister |
| Head Diameter: | 0.250 Inches Minimum And 0.270 Inches Maximum |
| Head Height: | 0.106 Inches Minimum And 0.113 Inches Maximum |
| Hole Diameter: | 0.047 Inches Nominal |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.164 Inches |
| Hole Quantity: | 1 |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 170000 Pounds Per Square Inch |
| Screw Material: | Iron Alloy 660 |
| Screw Material Document And Classification: | Ams 5736 Assn Std Single Material Response |
| Head Hole Configuration Style: | Round |
| Thread Series Designator: | Unc |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/35622-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.