

Description

Fastener Length: 3-5/32", Hole Diameter: 3/64", Thread: 8-32, Thread Length: 0-63/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3562210
Minimum Qty (MOQ):	1 EA
NSN:	5305-00-106-6529
Schedule B:	7318.15.6080
ECCN:	EAR99



* See page 2 for technical characteristics

P/N 35622-10 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.980 Inches Minimum And 1.020 Inches Maximum
Fastener Length:	3.150 Inches Minimum And 3.170 Inches Maximum
Head Style:	Fillister
Head Diameter:	0.250 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.106 Inches Minimum And 0.113 Inches Maximum
Hole Diameter:	0.047 Inches Nominal
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Hole Quantity:	1
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	170000 Pounds Per Square Inch
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams 5736 Assn Std Single Material Response
Head Hole Configuration Style:	Round
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/35622-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.