



Military-Fasteners.com

P/N 35622-19

Description

Fastener Length: 2-1/4", Hole Diameter: 3/64", Thread: 8-32, Thread Length: 49/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3562219
Minimum Qty (MOQ):	1 EA
NSN:	5305-00-106-6530
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N 35622-19 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.730 Inches Minimum And 0.770 Inches Maximum
Fastener Length:	2.240 Inches Minimum And 2.260 Inches Maximum
Head Style:	Fillister
Head Diameter:	0.250 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.106 Inches Minimum And 0.113 Inches Maximum
Hole Diameter:	0.047 Inches Nominal
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Hole Quantity:	1
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	170000 Pounds Per Square Inch
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams 5736 Assn Std Single Material Response
Head Hole Configuration Style:	Round
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/35622-19> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.