

Description

Fastener Length: 1-", Thread: 1/4-28, Thread Length: 25/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | 3662032 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-00-840-3578 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N 36-6203-2 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.380 Inches Minimum And 0.400 Inches Maximum |
| Fastener Length: | 1.030 Inches Nominal |
| Head Style: | Hexagon |
| Head Height: | 0.150 Inches Nominal |
| Width Between Flats: | 0.500 Inches Nominal |
| Shoulder Diameter: | 0.309 Inches Minimum First Shoulder And 0.312 Inches Maximum First Shoulder |
| Shoulder Length: | 0.330 Inches Nominal First Shoulder |
| Nominal Thread Diameter: | 0.250 Inches |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Shoulder Shape: | Round First Shoulder |
| Material: | Steel Comp 4340 Overall |
| Material Document And Classification: | Mil-s-5000 Mil Spec Single Material Response Overall Or Mil-s-5626 Mil Spec Single Material Response Overall |
| Thread Series Designator: | Unf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/36-6203-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.