

Description

Fastener Length: 1-", Thread: 1/4-28, Thread Length: 25/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3662032
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-840-3578
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N 36-6203-2 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.380 Inches Minimum And 0.400 Inches Maximum
Fastener Length:	1.030 Inches Nominal
Head Style:	Hexagon
Head Height:	0.150 Inches Nominal
Width Between Flats:	0.500 Inches Nominal
Shoulder Diameter:	0.309 Inches Minimum First Shoulder And 0.312 Inches Maximum First Shoulder
Shoulder Length:	0.330 Inches Nominal First Shoulder
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Shoulder Shape:	Round First Shoulder
Material:	Steel Comp 4340 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec Single Material Response Overall Or Mil-s-5626 Mil Spec Single Material Response Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/36-6203-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.