

Description

Thread Size: 7/64", Length: 29/32", Thread Length: 3/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3650192
Minimum Qty (MOQ):	1 EA
NSN:	5307-00-317-5031
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N 365019-2 Specifications

Thread Class:	3a Nut Thread
Thread Class:	3a Stud Thread
Thread Direction:	Left-hand Stud Thread
Thread Direction:	Right-hand Nut Thread
Thread Length:	0.170 Inches Minimum Nut Thread And 0.230 Inches Maximum Nut Thread
Shoulder Diameter:	0.250 Inches Nominal
Shoulder Length:	0.040 Inches Minimum And 0.050 Inches Maximum
Overall Length:	0.850 Inches Minimum And 0.970 Inches Maximum
Thread Quantity Per Inch:	40 Nut Thread
Thread Quantity Per Inch:	40 Stud Thread
Hardness Rating:	31.0 Rockwell C Minimum And 39.0 Rockwell C Maximum
Nominal Thread Size:	0.112 Inches Nut Thread
Nominal Thread Size:	0.112 Inches Stud Thread
Stud End Shank Diameter:	0.110 Inches Nominal
Surface Finish:	125.0 Microinches Overall
Material:	Steel
Material Document And Classification:	Ams 5643 Assn Std Single Material Response
Style Designator:	Shouldered
Thread Series Designator:	Unc Nut Thread
Thread Series Designator:	Unc Stud Thread

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/365019-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.