

P/N 3D0005-3-20

Military-Fasteners.com

#### Description

Fastener Length: 1-17/64", Thread: 10-32, Thread Length: 1-13/64"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

### **Additional Information**

SKU / Model:	3D0005320
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-329-9954
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



# P/N 3D0005-3-20 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.208 Inches Nominal
Fastener Length:	1.224 Inches Minimum And 1.271 Inches Maximum
Head Style:	Hexagon
Head Height:	0.105 Inches Minimum And 0.120 Inches Maximum
Width Between Flats:	0.305 Inches Minimum And 0.314 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Titanium Alloy Uns R56400
Screw Material Document And Classification:	Ams 4928 Assn Std Single Material Response Or Ams 4967 Assn Std Single Material Response
Bearing Surface Of Head Surface Finish:	63.0 Microinches
Shank Surface Finish:	32.0 Microinches
Thread Surface Finish:	32.0 Microinches
Thread Series Designator:	Unjf

## How to Order

Order this screw from our inventory online by visiting <u>https://military-fasteners.com/screws/machine+screws/3D0005-3-20</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.