

Description

Fastener Length: 1-17/64", Thread: 10-32, Thread Length: 1-13/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | 3D0005320 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-01-329-9954 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N 3D0005-3-20 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.208 Inches Nominal |
| Fastener Length: | 1.224 Inches Minimum And 1.271 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.105 Inches Minimum And 0.120 Inches Maximum |
| Width Between Flats: | 0.305 Inches Minimum And 0.314 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Screw Material: | Titanium Alloy Uns R56400 |
| Screw Material Document And Classification: | Ams 4928 Assn Std Single Material Response Or Ams 4967 Assn Std Single Material Response |
| Bearing Surface Of Head Surface Finish: | 63.0 Microinches |
| Shank Surface Finish: | 32.0 Microinches |
| Thread Surface Finish: | 32.0 Microinches |
| Thread Series Designator: | Unjf |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3D0005-3-20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.