

P/N 3D0005-3-37

Description

Military-Fasteners.com

Fastener Length: 2-5/16", Thread: 10-32, Thread Length: 2-5/16"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

| SKU / Model: | 3D0005337 |
|--------------------|------------------|
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5305-01-357-5869 |



P/N 3D0005-3-37 Specifications

| Thread Class: | За |
|---|--|
| Thread Direction: | Right-hand |
| Thread Length: | 2.160 Inches Minimum And 2.312 Inches Maximum |
| Fastener Length: | 2.222 Inches Minimum And 2.312 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.105 Inches Minimum And 0.120 Inches Maximum |
| Width Between Flats: | 0.305 Inches Minimum And 0.314 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Screw Material: | Titanium Alloy Uns R56400 |
| Screw Material Document And Classification: | Ams4928 Assn Std Single Material Response Or Ams4967 Assn Std Single Material Response |
| Bearing Surface Of Head Surface Finish: | 32.0 Microinches |
| Shank Surface Finish: | 32.0 Microinches |
| Thread Surface Finish: | 32.0 Microinches |
| Thread Series Designator: | Unjf |

How to Order

Order this screw from our inventory online by visiting <u>https://military-fasteners.com/screws/machine+screws/3D0005-3-37</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.