

**Description**

Fastener Length: 17/32", Thread: 10-32, Thread Length: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	3D000538
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-330-7865
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi

NO IMAGE  
AVAILABLE

## P/N 3D0005-3-8 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.500 Inches Nominal
<b>Fastener Length:</b>	0.484 Inches Minimum And 0.531 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.105 Inches Minimum And 0.120 Inches Maximum
<b>Width Between Flats:</b>	0.305 Inches Minimum And 0.314 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Screw Material:</b>	Titanium Alloy Uns R56400
<b>Screw Material Document And Classification:</b>	Ams 4928 Assn Std Single Material Response Or Ams 4967 Assn Std Single Material Response
<b>Bearing Surface Of Head Surface Finish:</b>	63.0 Microinches
<b>Shank Surface Finish:</b>	32.0 Microinches
<b>Thread Surface Finish:</b>	32.0 Microinches
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3D0005-3-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.