

Description

Fastener Length: 1-47/64", Thread: 1/4-24, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	3D0030520
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-455-2707
Schedule B:	7508.90.5000
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N 3D0030-5-20 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.467 Inches Nominal
Fastener Length:	1.704 Inches Minimum And 1.734 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.573 Inches Minimum And 0.635 Inches Maximum
Grip Diameter:	0.311 Inches Minimum And 0.312 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.312 Inches
Grip Length:	1.240 Inches Minimum And 1.260 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	132000 Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Material:	Cobalt Alloy Mp-159 Overall
Material Document And Classification:	Ams5842 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/3D0030-5-20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.