

Description

Fastener Length: 1-47/64", Thread: 1/4-24, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | 3D0030520 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5305-01-455-2707 |
| Schedule B: | 7508.90.5000 |
| ECCN: | EAR99 |

NO IMAGE
AVAILABLE

P/N 3D0030-5-20 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.467 Inches Nominal |
| Fastener Length: | 1.704 Inches Minimum And 1.734 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.573 Inches Minimum And 0.635 Inches Maximum |
| Grip Diameter: | 0.311 Inches Minimum And 0.312 Inches Maximum |
| Internal Drive Style: | Offset Cruciform (torque Set) |
| Nominal Thread Diameter: | 0.312 Inches |
| Grip Length: | 1.240 Inches Minimum And 1.260 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 132000 Pounds Per Square Inch |
| Countersink Angle: | 100.0 Degrees Nominal |
| Material: | Cobalt Alloy Mp-159 Overall |
| Material Document And Classification: | Ams5842 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/3D0030-5-20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.