

Description

Fastener Length: 39/64", Thread: 8-32, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | 3D00680810 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-01-419-6024 |
| Schedule B: | 8108.90.3060 |
| ECCN: | 9A991 |
| National Motor Freight: | 093490, Bolt / Nut / Screw / Clips / Fastener / Etc |

NO IMAGE
AVAILABLE

P/N 3D0068-08-10 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.558 Inches Maximum |
| Fastener Length: | 0.560 Inches Minimum And 0.620 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.296 Inches Minimum And 0.331 Inches Maximum |
| Internal Drive Style: | Cross Recess Type Iii |
| Nominal Thread Diameter: | 0.164 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Screw Material: | Titanium Alloy Uns R56400 |
| Screw Material Document And Classification: | Ams 4928 Assn Std Single Material Response Or Ams 4967 Assn Std Single Material Response |
| Thread Series Designator: | Unjc |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/3D0068-08-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.